

2024 AGRICULTURAL LIVESTOCK HIGH-EFFICIENCY VENTILATION SYSTEMS IOWA REBATE CLAIM FORM

Rebates are issued on a first-come, first-served basis. Rebates and incentives are offered until approved funds are exhausted or through Dec. 31, 2024, whichever comes first. Submission of claim form does not guarantee payment. Alliant Energy reserves the right to modify or end this rebate program at any time without prior notice.

INSTRUCTIONS: Fill out form completely, sign and include copy of receipts. Failure to complete the form and provide documentation could result in claim being sent back or denied.

This rebate is for equipment installed Jan. 1-Dec. 31, 2024.

Alliant Energy is the trade name of Interstate Power and Light Company (IPL). The utility providing the rebates is Interstate Power and Light Company (IPL), an Alliant Energy company, hereinafter referred to as Alliant Energy.

If you have questions or need assistance with this form, call our Alliant Energy Agriculture representative at 319-237-3856. Or email at AlliantEnergyAg@franklinenergy.com

CUSTOMER INFORMATION					
Rebate Applicant Information			Building Information		
Person or Company Receiving Rebate			Installation Address		
Applicant Email Address			City	State IOWA	ZIP
Mailing Address			Alliant Energy Account No. at Installation Address		
City	State	ZIP	<div style="display: flex; justify-content: space-between;"> [] [] [] [] [] [] [] [] [] [] </div>		
Primary Contact Person for Claims Questions		Phone No. ()	Application Type <input type="checkbox"/> Swine <input type="checkbox"/> Dairy <input type="checkbox"/> Poultry <input type="checkbox"/> Other _____		
Applicant Tax Status (required) All applicants must provide a copy of a W-9 showing the Social Security Number or Employer Identification Number and the legal name associated with the number provided on the document. To comply with IRS regulations, the applicant must provide a copy of a W-9 each time a claim is submitted.					
<input type="checkbox"/> Sole proprietor <input type="checkbox"/> Partnership <input type="checkbox"/> Government <input type="checkbox"/> Nonprofit <input type="checkbox"/> Corporation <input type="checkbox"/> Religious					
All rebates are subject to program rules. Each project is limited to a maximum of \$25,000 for electric customers and \$2,500 for gas customers. Electric customers are limited to an annual maximum amount of \$250,000 and gas customers are limited to an annual maximum of \$25,000.					

Claim forms are due by Jan. 31, 2025

Additional information continued

EXISTING BUILDING HIGH-EFFICIENCY VENTILATION FANS
 Wall-mounted fans operate under static pressure, draw in fresh air and exhaust air from a facility.
 If fan is controlled by a new thermostat/environmental controller, complete thermostat section below.
 Must be tested by AMCA or BESS and rated at 0.05" static pressure.

Fan Type	Fan Size	CFM/Watt	Brand Name	Model No.	Equipment Cost	Qty	Install Date	No. of Fans	Total Rebate
14"-23" fan with minimum 10.1 cfm per watt or higher					\$			_____ x \$45	\$
24"-35" fan with minimum 13.5 cfm per watt or higher					\$			_____ x \$75	\$
36"-47" fan with minimum 17.4 cfm per watt or higher					\$			_____ x \$125	\$
48" or larger fans with minimum 20.3 cfm per watt or higher					\$			_____ x \$150	\$

THERMOSTAT/PROGRAMMABLE CONTROLLER (existing buildings only)

Brand Name _____ Model No. _____ Equipment Cost \$ _____ Install Date _____

Number of fans controlled: 14"-23" # _____ 24"-35" # _____ 36"-47" # _____ 48" plus # _____

\$20 rebate per fan controlled TOTAL NUMBER OF FANS _____ x \$20 = \$ _____ REBATE

Total Fan Rebate \$ _____ + Thermostat Controller Rebate \$ _____ = \$ _____ Total Rebate

NEW CONSTRUCTION HIGH-EFFICIENCY VENTILATION FANS
 Wall-mounted fans operate under static pressure, draw in fresh air and exhaust air from a facility.
 Must be tested by AMCA or BESS and rated at 0.05" static pressure.

Fan Type	Fan Size	CFM/Watt	Brand Name	Model No.	Equipment Cost	Qty	Install Date	No. of Fans	Total Rebate
14"-23" fan with minimum 10.1 cfm per watt or higher					\$			_____ x \$25	\$
24"-35" fan with minimum 13.5 cfm per watt or higher					\$			_____ x \$45	\$
36"-47" fan with minimum 17.4 cfm per watt or higher					\$			_____ x \$75	\$
48" or larger fans with minimum 20.3 cfm per watt or higher					\$			_____ x \$90	\$

REMEMBER TO SIGN THE NEXT PAGE

Additional information continued 

Claim forms are due by Jan. 31, 2025

ECM VENTILATION FAN AND STAGING CONTROLS

System must include controller with temperature and voltage (for fan speed) settings, wired for 208-volt or 240-volt service. Systems with existing ventilation controllers are not eligible for prescriptive rebates and should apply for a custom rebate.

Must be tested by AMCA or BESS and rated at 0.05" static pressure.


Please fill out the following table with fan information, followed by a corresponding operating profile table for each size fan.

AC permanent magnet fans must be preapproved through a custom rebate.

DC permanent magnet fans only

Fan Type	Fan Size	Rated Fan Wattage (at full speed 0.05 static pressure)	Brand Name	Model No.	Existing Temperature Control Strategy	Equipment Cost	Qty	No. of Fans		Total Rebate
								EXISTING CONSTRUCTION	NEW CONSTRUCTION	
14"-23" ECM Ventilation Fan					<input type="checkbox"/> None <input type="checkbox"/> On/off staging control	\$		_____ x \$150	_____ x \$90	\$
24"-35" ECM Ventilation Fan					<input type="checkbox"/> None <input type="checkbox"/> On/off staging control	\$		_____ x \$250	_____ x \$150	\$
36"-47" ECM Ventilation Fan					<input type="checkbox"/> None <input type="checkbox"/> On/off staging control	\$		_____ x \$420	_____ x \$250	\$
≥ 48" ECM Ventilation Fan					<input type="checkbox"/> None <input type="checkbox"/> On/off staging control	\$		_____ x \$500	_____ x \$300	\$

REMEMBER TO SIGN THE NEXT PAGE

Additional information continued 

Claim forms are due by Jan. 31, 2025

OPERATING PROFILE FOR 14-23 INCH ECM FANS			
Number of fans	Temperature bin	Annual operating hours	Fan speed (%)
	≥ 70 F		
	≥ 60 F and <70 F		
	≥ 55 F and <60 F		
	≥ 50 F and <55 F		
	<50 F		

OPERATING PROFILE FOR 24-35 INCH ECM FANS			
Number of fans	Temperature bin	Annual operating hours	Fan speed (%)
	≥ 70 F		
	≥ 60 F and <70 F		
	≥ 55 F and <60 F		
	≥ 50 F and <55 F		
	<50 F		

OPERATING PROFILE FOR 36-47 INCH ECM FANS			
Number of fans	Temperature bin	Annual operating hours	Fan speed (%)
	≥ 70 F		
	≥ 60 F and <70 F		
	≥ 55 F and <60 F		
	≥ 50 F and <55 F		
	<50 F		

OPERATING PROFILE FOR ≥ 48 INCH ECM FANS			
Number of fans	Temperature bin	Annual operating hours	Fan speed (%)
	≥ 70 F		
	≥ 60 F and <70 F		
	≥ 55 F and <60 F		
	≥ 50 F and <55 F		
	<50 F		

IN ABSENCE OF OTHER DATA, USE THE DEFAULT HOURS FROM THE EXAMPLE PROBLEM FOR EACH TEMPERATURE RANGE.

EXAMPLE:
 A DAIRY STALL BARN REPLACED 30 EXISTING, 42-INCH DIAMETER, SINGLE-SPEED VENTILATION FANS WITH 30, 42-INCH DIAMETER, HIGH EFFICIENCY ECM VENTILATION FANS WITH INTEGRATED CONTROLS THAT CAN VARY THE SPEED OF THE FANS. THE EFFICIENT ECM VENTILATION FANS HAVE A RATED WATTAGE OF 565 WATTS AT FULL SPEED. THE SET CONTROL STRATEGY, AS PROGRAMMED BY THE INSTALLER, IS AS FOLLOWS:

Number of fans	Temperature bin	Annual operating hours	Fan speed (%)
30	≥ 70 F	2,099	100%
20	≥ 60 F and <70 F	2,230	75%
15	≥ 55 F and <60 F	1,115	75%
15	≥ 50 F and <55 F	1,115	50%
8	<50 F	2,202	100%

REMEMBER TO SIGN THE NEXT PAGE

Additional information continued 

Claim forms are due by Jan. 31, 2025

